RICH BASE RKB-6869S

HBATTURE

- Fully compatible for Windows 10 and 11
- Built-in Smart Card Reader (SCR)



Key Numbers	Key Switch Mechanism
104/105/108 keys (US/EU/JP)	Membrane key switch with 10 million life cycle time
Key Force	Total Travel Distance
50 ± 7g	4 ± 0.4 mm
Interface	Product Dimensions
USB	443 X 140.5 X 31.5 mm
Input Power	Cable Length
5Vdc, < 100mA	1670mm
Operating Temperature	Product Weight
0°C to 50°C	800 g
Storage Temperature	Smartcard Reader
-10°C to 60°C	• EMV 4.0 Level 1 SPEC certified
Key Prints	PBOC 2.0 Level 1 certified Paged on ISO7816 implementation
Laser printing	 Based on ISO7816 implementation Support PC smart Card industry standard – PC/SC 2.0
Product Approvals	Support Microsoft Smart Card for Windows
• FCC F© • CE (€	 Meet Microsoft WHQL USB Smart Card Reader requirements Support single slot Support T0, T1 protocol Support ISO7816 Class A, B and C (5V/3V/1.8V) card



Smartcard Reader

- Support software update for memory card module
- Support Direct Web Page Link via configuration in external EEPROM
- Support short APDU and extended APDU